

IOT-C51x series LoRaWAN® wireless solenoid valve controller is a device used to remotely control DC latching solenoids of the valve. It contains 2 solenoid interfaces and 1 pulse interface, which can be easily controlled locally or remotely. Besides ultra-low-power LoRaWAN® technology, IOT-C51x series also provides both solar and built-in battery power supply for uninterrupted operation. For outdoor applications, it equips with IP67-rated enclosure and M12 connectors to protect from water and dust under harsh environments.

## ◆ Features

- Compatible with standard DC latching solenoids
- OPEN/CLOSE control by mobile APP locally or commands remotely
- One pulse water meter interface for flow monitoring
- Transmission distance up to 11km with line of sight
- Waterproof design including IP67 case and M12 connectors
- Solar powered and built-in chargeable battery
- Quick wireless configuration via NFC
- Time and flow control via Milesight IoT Cloud

## ◆ Specifications

### Wireless Transmission

Technology	LoRaWAN®
Frequency	CN470/IN865/EU868/RU864/US915/AU915/KR920/AS923
Tx Power	16dBm(868)/20dBm(915)/19dBm(470)
Sensitivity	-137dBm @300bps
Working Mode	UC511: Class A, Class C UC512: Class A

### Data Interfaces

Interface Type	M12 A-Coded Male
----------------	------------------

### Solenoid Interface

Ports	2 × Solenoid Interfaces
Solenoid Support	2 wires 12V DC latching solenoids
Cable Length	1.5m (by default)

### Pulse Interface

Ports	2 × Pulse Interfaces, support 2 pulse meters
Logical Level	Low: 0~0.9V, High: 2.5~3.3V
Cable Length	1.5m (by default)

### Operation

Power On & Off	Mobile APP(via NFC), PC software(via USB Type-C), power button (Internal), Cable Connection
Configuration	Mobile APP(via NFC) or PC software(via USB Type-C)

### Physical Characteristics

Operating Temperature	-20°C to +60°C
Ingress Protection	IP67
Dimension	120.1 × 120.1 × 55.4 mm (4.73 × 4.73 × 2.18 in)
Power Connector	M12 A-Coded Male
Power Supply	1. Solar powered + Rechargeable battery + 5-24 VDC supply 2. 19000mAh replaceable Li-SOCL <sub>2</sub> battery
Installation	Wall or Pole Mounting

## ◆ Ordering Information

Model	Power Supply
UC511-DI-868M	<ol style="list-style-type: none"> <li>1. Solar powered (5V, 1W)</li> <li>2. 2 × 2550mAh chargeable battery</li> <li>3. 5-24 VDC powered by M12 connector</li> </ol>
UC512-DI-868M	19000mAh replaceable Li-SoCl <sub>2</sub> battery
<p><b>Remark:</b></p> <p>"-915M"/"-868M"/"-470M" in the model refers to different LoRaWAN® Frequency in option for different countries/regions, (e.g.)</p> <p>"-915M": KR920/AS923/AU915/US915</p> <p>"-868M": IN865/EU868/RU864</p> <p>"-470M": CN470</p>	